Size Chart











dium La

Extra Large

PlexiDor	Weight	Breed Size Examples	Type of	Opening	Installation	Overall
Size	of Pet		Installation	for Pet	Cut Hole	Dimensions‡
Small SM	Up to 9 l bs (Dog) 24 l bs (Cat)	Cats, Chihuahuas, Pomeranians, Papillons, Yorkies, Maltese and Japanese Chins	Door Series Wall Series	6½" x 7¼" 6½" x 7¼"	8¾" x 85%" 8¾" x 95%"†	97%" x 97%" 103%" x 117%"
Medium	Up to	Poodles, Corgis, Dachshunds, Beagles, Pekingese, Shelties,	Door Series	9" x 12"	11½" x 13¾"	13¾" x 15¼"
MD	40 l bs	Schnauzers, Cocker Spaniels and most Terriers	Wall Series	9" x 12"	11%" x 14¾"†	14¾" x 17¾"
Large	Up to	Labradors, German Shepherds, Golden Retrievers, Boxers,	Door Series	11¾" x 16"	14¼" x 175/8"	16½" x 19¼"
LG	100 lbs	Collies, Setters, Bulldogs, Pointers and Dobermans	Wall Series	11¾" x 16"	143/8" x 183/8"†	16½" x 20½"
Extra Large	Up to	Great Danes, St. Bernards, Rottweiler, Old English Sheepdogs,	Door Series	15¾" x 23½"	181⁄8″ x 251⁄4″	20½" x 26¾"
XL	220 l bs	Newfoundlands, Irish Wolfhounds and Great Pyrenees	Wall Series	15¼" x 23½"	181⁄2″ x 261⁄4″†	21%" x 28%"
Electronic	Up to	Large breed examples as listed including Malamutes,	Door Series	125%" x 195%"	14¼" x 21¾"	171⁄8″ x 545⁄8″
PDE	125 lbs	Weimaraners, Rhodesian Ridgebacks and all Cats	Wall Series	125%" x 195%"	14¼" x 23"†	171⁄8″ x 545⁄8″

† Note: There are two dimensions for the Wall Series cut hole, interior and exterior. Read the installation instructions carefully before cutting. ‡ Dimensions listed in chart are Width by Height.

Medium

Installation Height The installation distance from frame to floor.

Installing your PlexiDor Pet Door at the correct height will ensure the door is comfortable for your pet to use. Stepping up and through the door is best.

Important: The suggested measurements are a guide only. Make sure the pet door is installed so that the opening is at least two inches above the pet's back.

From bottom of frame











12"-14"

Frame Colors

White

Silver

Bronze

Have questions about the size that's right for your pet? Call us at 800-749-9609